


























































<b>Fall Arresters</b>	
<b>Fall Arrester To Suit 14-16mm Polyamide Twisted Rope</b> Model: FA 20 100 00 A <ul style="list-style-type: none"> <li>• All ropes supplied separately.</li> <li>• 10 mtr rope (Model:FA 20 100 10).</li> <li>• 20 mtr rope (Model:FA 20 100 20).</li> <li>• Longer lengths available. • Unique non-inverting system to prevent installing the device upside down.</li> </ul> 	<b>Fall Arrester To Suit 14-16mm Polyamide Twisted Rope With Shock Absorber</b> Model: FA 20 100 00 B <ul style="list-style-type: none"> <li>• All ropes supplied separately.</li> <li>• 10 mtr rope (Model:FA 20 100 10).</li> <li>• 20 mtr rope (Model:FA 20 100 20).</li> <li>• Longer lengths available.</li> <li>• Unique non-inverting system to prevent installing the device upside down.</li> </ul> 
<b>Polyamide twisted rope</b> Model: FA 20 100 99 FA 20 101 99 Colored tracer strand losing colour which shows the lanyard is unfit for use Manufactured ends (loops + endings) on request	<b>Captive Fall Arrester Attached to 12mm x 20 mtr Kernmantle Rope With Shock Absorber</b> Model: FA 20 102 20 <ul style="list-style-type: none"> <li>• 10 mtr rope (Model:FA 20 102 10).</li> <li>• Rope lengths available from 5 mtrs to 100 mtrs.</li> <li>• Rope ends protected by strong transparent sleeve which makes the stitching visible for easy inspection prior to use.</li> </ul> 
<b>Polyamide Kernmantle rope</b> Model: FA 20 102 99 FA 20 103 99 Static rope Colored tracer strand losing colour which shows the lanyard is unfit for use	<b>Rope Grab</b> Model: FA 20 200 00 Works on rigid or flexible stainless steel cable system 
<b>Rope Grab</b> Model: FA 20 200 01 Works on rigid stainless steel cable system 	<b>Wire Rope</b> Model: FA 20 200 99 Stainless steel, diameter 8mm, 7x19 
<b>Mounting Brackets</b> Model: FA 20 201 00 Supplied with mounting hardware, this piece (high or low) fixes on square profiles, round profiles, U, H, T, L.... Breaking strength > 10 kN 	<b>Intermediate Cable Guide</b> Model: FA 20 202 00 Maintains the cable along the scale and allows the rope grab to pass through without any manipulation. This cable guide is used to avoid the cable flapping. Installed every 8 mts. 
<b>End Clamp</b> Model: FA 20 203 00 Maintains the cable at the bottom of the ladder to prevent the counterweight to beat on the ladder under the effect of the wind. 	<b>Dead Weight</b> Model: FA 20 204 00 <ul style="list-style-type: none"> <li>• To ensure a minimum tension on the cable.</li> <li>• Weight : 6 kg.</li> </ul> 

<p><b>Tensioner</b></p>	<p><b>Shock Absorber</b></p>
<p>Model: FA 20 205 00</p> <p>Regulates the tensioning of cable (tension about 80 daN) by simple rotation</p> 	<p>Model: FA 20 206 00</p> <p>Necessary to reduce the impact force due to the arrest of the fall in the facility.</p> 
<p><b>Cable Extremity</b></p>	<p><b>Retractable fall arrest with a 50 mm webbing</b></p>
<p>Model: FA 20 207 00</p> <p>Allows the crimping of the cable at the desired length and eliminates the danger of any loose wire.</p> 	<p>Model: FA 20 300 02</p> <p>Maximum length: 2.50m Incorporate a protective casing , an Energy Absorber (45 mm) and a Steel Karabiner FA 50 101 17 for Harness end as attachment elements. Minimum breaking strength&gt; 15kN</p> 
<p><b>Retractable Fall Arrest Block</b></p>	<p><b>Olympe Retractable Fall Arrest Block</b></p>
<p>Model: FA 20 301 02</p> <ul style="list-style-type: none"> <li>• 2.5 mtr (Model: FA 20 301 02).</li> <li>• 50mm webbing.</li> <li>• Protective casing.</li> <li>• Incorporates a shock absorber.</li> <li>• Swivel eye load indicator at top.</li> <li>• Snap hook at bottom.</li> <li>• Also available with karabiner at bottom (Model: FA 20 300 02).</li> <li>• Minimum breaking strength 15 kN.</li> </ul> 	<p>Model: FA 20 400 06</p> <ul style="list-style-type: none"> <li>• 6 mtr (Model:FA 20 400 06).</li> <li>• 10 mtr (Model:FA 20 400 10).</li> <li>• 15 mtr (Model:FA 20 400 15).</li> <li>• 20 mtr (Model:FA 20 400 20).</li> <li>• 30 mtr (Model:FA 20 400 30).</li> <li>• Outer casing made from high resistant polymer.</li> <li>• Minimum breaking strength 15 kN.</li> <li>• Fitted with karabiner at top.</li> <li>• Swivel snap hook with load indicator at bottom.</li> <li>• Galvanised steel wire rope 4.8mm.</li> </ul> 
<p><b>OLYMPE cable, retractable fall arrest 10 and 15 m</b></p>	<p><b>OLYMPE cable, retractable fall arrest 20, 25 and 30 m</b></p>
<p>Model: FA 20 400 10 FA 20 400 15</p> <p>Casing made up of high impact strength Polymer, to prevent breakage and is nearly indestructible. Comes with Galvanized Steel Wire Rope of diam 4.8 mm. FA 50 101 17 at anchorage end FA 50 203 11 at attachment end. FA 50 203 11 connector with load indicator. Minimum breaking strength&gt; 12kN</p> 	<p>Model: FA 20 400 20 FA 20 400 25 FA 20 400 30</p> <p>Casing made up of high impact strength Polymer, to prevent breakage and is nearly indestructible. Comes with Galvanized Steel Wire Rope of diam 4.8 mm. FA 50 101 17 at anchorage end FA 50 203 11 at attachment end. FA 50 203 11 connector with load indicator. Minimum breaking strength&gt; 12kN HORIZONTAL USE : The retractable fall arresters OLYMPE with polymer casing and steelwire rope are approved for horizontal use when it is used with a polyamid lanyard connected to the cable self retracting lifeline.</p> 
<p><b>OLYMPE cable, retractable fall arrest 2 m</b></p>	<p><b>Olympe Retractable Fall Arrest Block</b></p>
<p>Model: FA 20 500 02</p> <p>Casing made up of aluminium alloy. Comes with a 25 mm polyester webbing. Include two FA 50 207 55 at anchorage end. USE : To be used wherever the user needs a greater freedom of movement and pass obstacles remaining secure permanently. Minimum breaking strength&gt; 15kN</p> 	<p>Model: FA 20 500 03</p> <ul style="list-style-type: none"> <li>• 3.5 mtr (Model: FA 20 500 03).</li> <li>• 25mm webbing.</li> <li>• Outer casing made from high impact resistant polymer.</li> <li>• Minimum breaking strength 15 kN.</li> <li>• Fitted with karabiner at top. • Swivel snap hook with load indicator at bottom.</li> </ul> 












<b>OLYMPE webbing, retractable fall arrest 6 m</b>	<b>OLYMPE webbing, retractable fall arrest 12 m</b>
<p>Model: FA 20 500 06</p> <p>Casing made up of high impact strength Polymer, to prevent breakage and is nearly indestructible. Comes with a 25 mm polyester webbing. FA 50 101 17 at anchorage end FA 50 203 11 at attachment end. FA 50 203 11 connector with load indicator. Minimum breaking strength &gt; 15kN</p> 	<p>Model: FA 20 500 12</p> <p>Casing made up of high impact strength Polymer, to prevent breakage and is nearly indestructible. Comes with a 25 mm polyester webbing. FA 50 101 17 at anchorage end FA 50 203 11 at attachment end. FA 50 203 11 connector with load indicator. Minimum breaking strength &gt; 15kN</p> 
<b>OLYMPE cable, retractable fall arrest 6 m</b>	<b>OLYMPE cable, retractable fall arrest 10, 15 m</b>
<p>Model: FA 20 600 06</p> <p>Casing made up of aluminium alloy. Comes with Galvanized Steel Wire Rope of diam 4.8 mm. FA 50 101 17 at anchorage end FA 50 203 11 at attachment end. FA 50 203 11 connector with load indicator. Minimum breaking strength &gt; 12kN</p> 	<p>Model: FA 20 600 10 FA 20 600 15</p> <p>Casing made up of aluminium alloy. Comes with Galvanized Steel Wire Rope of diam 4.8 mm. FA 50 101 17 at anchorage end FA 50 203 11 at attachment end. FA 50 203 11 connector with load indicator. Minimum breaking strength &gt; 12kN</p> 
<b>Polyamide Thimble</b>	<b>Counterweight</b>
<p>Model: FA 20 900 00</p> <p>for rope diam: ???? mm</p> 	<p>Model: FA 20 901 00</p> <p>For rope from Diam 9 mm to 18 mm Weight : 0,7 kg</p> 
<h2 style="text-align: center;">Lanyards</h2>	
<b>Restraint Twisted Rope Lanyards</b>	<b>Polyamide Lanyard For Horizontal Use</b>
<p>Model: FA 40 100 15</p> <ul style="list-style-type: none"> <li>• 12mm polyamide twisted rope with thimble eye at each end.</li> <li>• Loops protected by abrasion resistant thimbles.</li> <li>• Stitching protected by strong transparent sleeve.</li> <li>• Minimum breaking strength 22 kN as per EN 354:2002</li> </ul> 	<p>Model: FA 40 304 15</p> <ul style="list-style-type: none"> <li>• For use only with Kratos safety Olympe fall arrest block with polymer casing and steel wire rope which are approved for horizontal use when used with polyamide lanyard connected to the cable self retracting lifeline.</li> </ul> 
<b>Restraint Kernmantle Lanyards</b>	<b>'Y' Forked Kernmantle Rope Lanyard 1.5 mtr</b>
<p>Model: FA 40 500 15</p> <ul style="list-style-type: none"> <li>• 12mm kernmantle rope with thimble eye each end. • Loops protected by abrasion resistant thimbles.</li> <li>• Stitching protected by strong transparent sleeve.</li> <li>• Minimum breaking strength 22 kN as per EN 354:2002</li> </ul> 	<p>Model: FA 40 600 15</p> <ul style="list-style-type: none"> <li>• 12mm kernmantle rope with snap hook at one end and scaffold hooks at the other ends.</li> <li>• Loops protected by abrasion resistant thimbles.</li> <li>• Stitching protected by strong transparent sleeve.</li> <li>• Minimum breaking strength 22 kN as per EN 354:2002</li> </ul> 
<b>Restraint Expandable Rope Lanyards</b>	<b>Work Positioning Lanyard with ring adjuster</b>
<p>Model: FA 40 700 20</p> <p>The Lanyards are ideal for usage in conditions where there are chances for the user tripping over the Lanyard The elastic nature of the lanyard reduces the actual effective length of the Lanyard thereby reducing the hazards Made up of 44mm wide Expandable Lanyard</p> 	<p>Model: FA 40 900 20</p> <p>Made up of 14mm diam polyamide3- strand twisted rope Abrasion resistant thimble to protect the loop from being damaged by metallic contact Forged alloy steel ring-adjuster Maximum Length is 2 mtrs Provided with screw locking karabiner FA 50 101 17 at both ends for attachment</p> 

Expandable Length : 1,5m or 2 m Relaxed Length: 1.4m Loops protected by an abrasion resistant tubular webbing. Breaking Strength is 22 kN as per the norm EN 354:2002	
<b>Adjustable Work Positioning Webbing Lanyard 2.0 mtr</b>	<b>Adjustable Work Positioning Kernmantle Rope Lanyard 2.0 mtr</b>
Model: FA 40 901 20  <ul style="list-style-type: none"> <li>• 33mm webbing with karabiner at each end</li> <li>• Alloy steel ring adjuster</li> </ul> 	Model: FA 40 902 20  <ul style="list-style-type: none"> <li>• 12mm kernmantle rope with karabiner at each end</li> <li>• Loops protected by abrasion resistant thimbles</li> <li>• Alloy steel ring adjuster</li> </ul> 
<b>Work Positioning Lanyard with Grip adjuster</b>	<b>Work Positioning Lanyard with Grip adjuster</b>
Model: FA 40 903 20  <p>Made up of 12mm diam polyamide kernmantle rope Abrasion resistant thimble to protect the loop from being damaged by metallic contact Steel rope grab adjuster for a progressive movement Maximum Length is 2 mtrs Provided with screw locking karabiner FA 50 101 17 at both ends for attachment</p> 	Model: FA 40 904 20  <p>Made up of 14mm diam polyamide3- strand twisted rope Abrasion resistant thimble to protect the loop from being damaged by metallic contact Stainless steel rope grab adjuster, for an easy one hand length adjustment Maximum Length is 2 mtrs Provided with screw locking karabiner FA 50 101 17 at both ends for attachment</p> 
<b>Tools Lanyard</b>	<b>Protection Sleeve</b>
Model: FA 90 001 00  <ul style="list-style-type: none"> <li>• Designed to attach tools to the user or an anchor point.</li> </ul> 	Model: FA 90 002 00  
<b>Harnesses</b>	
<b>Fly'in1 - 2 Point Luxury Full Body Harness</b>	<b>Single Point Full Body Harness</b>
Model: FA 10 101 00  <ul style="list-style-type: none"> <li>• Front &amp; rear attachment points.</li> <li>• Quick connect buckles.</li> <li>• Fully adjustable</li> </ul> 	Model: FA 10 102 00  <ul style="list-style-type: none"> <li>• Rear 'D' ring.</li> <li>• Adjustable thigh and chest strap.</li> </ul> 
<b>2 Point Full Body Harness</b>	<b>2 Point Full Body Harness</b>
Model: FA 10 103 00  <ul style="list-style-type: none"> <li>• Front &amp; rear attachment points.</li> <li>• Adjustable thigh and chest strap.</li> </ul> 	Model: FA 10 104 00  <ul style="list-style-type: none"> <li>• Front &amp; rear attachment points.</li> <li>• Fully adjustable.</li> </ul> 
<b>2 Point Comfort Full Body Harness</b>	<b>2 Point Full Body Harness</b>
Model: FA 10 104 01  <ul style="list-style-type: none"> <li>• Front &amp; rear attachment points.</li> <li>• Quick connect buckles.</li> <li>• Fully adjustable.</li> </ul> 	Model: FA 10 105 00  <ul style="list-style-type: none"> <li>• Front &amp; rear 'D' rings.</li> <li>• Fully adjustable</li> </ul> 









<b>Rescue Full Body Harness</b>	<b>Move1 - 2 Point Elasticated Full Body Harness</b>
<p>Model: FA 10 106 00</p> <ul style="list-style-type: none"> <li>• Front &amp; rear 'D' rings.</li> <li>• Extension rescue strap with top 'D' ring.</li> <li>• Fully adjustable</li> </ul> 	<p>Model: FA 10 107 00</p> <ul style="list-style-type: none"> <li>• Front &amp; rear 'D' rings.</li> <li>• Special stainless steel fittings.</li> <li>• Fully adjustable.</li> <li>• Elastic webbing for comfort and impact resistance.</li> </ul> 
<b>Single Point Full Body Harness</b>	<b>Fly'in2 - 4 Point Luxury Full Body Harness</b>
<p>Model: FA 10 108 00</p> <ul style="list-style-type: none"> <li>• Rear 'D' ring.</li> <li>• Fully adjustable.</li> </ul> 	<p>Model: FA 10 201 00</p> <ul style="list-style-type: none"> <li>• Front &amp; rear attachment points.</li> <li>• Work positioning belt with 2'D'rings.</li> <li>• Quick connect buckles.</li> <li>• Fully adjustable.</li> </ul> 
<b>Fly'in3 - 5 Point Luxury Full Body Harness</b>	<b>2 Point Full Body Harness</b>
<p>Model: FA 10 202 00</p> <ul style="list-style-type: none"> <li>• Front &amp; rear 'D' rings.</li> <li>• Work positioning belt with 2 'D' rings.</li> <li>• Waist level 'D' ring for rope access.</li> <li>• Quick connect buckles.</li> <li>• Fully adjustable.</li> </ul> 	<p>Model: FA 10 202 00</p> <ul style="list-style-type: none"> <li>• Front &amp; rear attachment points.</li> <li>• Incorporated with our work positioning belt (Model:FA 10 402 00) with 2 'D' rings.</li> <li>• Adjustable thigh &amp; chest straps.</li> </ul> 
<b>2 Point Full Body Harness</b>	<b>2 Point Comfort Full Body Harness</b>
<p>Model: FA 10 204 00</p> <ul style="list-style-type: none"> <li>• Front &amp; rear attachment points.</li> <li>• Incorporated with our work positioning belt (Model:FA 10 401 00) with 2 'D' rings.</li> <li>• Fully adjustable.</li> </ul> 	<p>Model: FA 10 204 01</p> <ul style="list-style-type: none"> <li>• Front &amp; rear attachment points.</li> <li>• Incorporated with our work positioning belt (Model:FA 10 401 00) with 2 'D' rings.</li> <li>• Fully adjustable.</li> <li>• Quick connect buckles.</li> </ul> 
<b>4 Point Full Body Harness</b>	<b>5 Point Comfort Full Body Harness</b>
<p>Model: FA 10 205 00</p> <ul style="list-style-type: none"> <li>• Front &amp; rear 'D' rings.</li> <li>• Work positioning belt with 2 'D' rings.</li> <li>• Fully adjustable.</li> </ul> 	<p>Model: FA 10 206 00</p> <ul style="list-style-type: none"> <li>• Front &amp; rear 'D' rings.</li> <li>• Work positioning belt with 2 'D' rings.</li> <li>• Waist level 'D' ring for rope access.</li> <li>• Fully adjustable.</li> </ul> 
<b>2 Point Full Body Harness</b>	<b>Move2 - 4 Point Elasticated Full Body Harness</b>
<p>Model: FA 10 207 00</p> <ul style="list-style-type: none"> <li>• Front &amp; rear attachment points.</li> <li>• Rotating work positioning belt with 2 'D' rings.</li> <li>• Quick connect buckles.</li> <li>• Fully adjustable.</li> </ul> 	<p>Model: FA 10 208 00</p> <ul style="list-style-type: none"> <li>• Front &amp; rear 'D' rings.</li> <li>• Work positioning belt with 2 'D' rings.</li> <li>• Special stainless steel fittings.</li> <li>• Fully adjustable.</li> <li>• Elastic webbing for comfort and impact resistance.</li> </ul> 

<b>2 Point Full Body Harness With Work Vest</b>	<b>2 Point Full Body Harness With Multi Pocket Work Vest</b>
<p>Model: FA 10 300 00</p> <ul style="list-style-type: none"> <li>• Front &amp; rear attachment points.</li> <li>• Adjustable chest &amp; thigh straps.</li> <li>• Grey work vest.</li> <li>• Adjustable zip system.</li> </ul>	<p>Model: FA 10 301 00</p> <ul style="list-style-type: none"> <li>• Front &amp; rear attachment points.</li> <li>• Fully adjustable.</li> <li>• Grey work vest.</li> <li>• Adjustable zip system.</li> </ul>
	
<b>2 Point High-Visibility Full Body Harness</b>	<b>2 Point High-Visibility Full Body Harness</b>
<p>Model: FA 10 302 00</p> <ul style="list-style-type: none"> <li>• Front &amp; rear attachment points.</li> <li>• Yellow work vest.</li> <li>• Fully adjustable.</li> <li>• Adjustable zip system.</li> </ul>	<p>Model: FA 10 303 00</p> <ul style="list-style-type: none"> <li>• Front &amp; rear attachment points.</li> <li>• Orange work vest.</li> <li>• Fully adjustable.</li> <li>• Adjustable zip system.</li> </ul>
	
<b>Comfortable Work Positioning Belt</b>	<b>Work Positioning Belt</b>
<p>Model: FA 10 401 00</p> <ul style="list-style-type: none"> <li>• 2 lateral 'D' rings for work positioning.</li> <li>• Fully adjustable.</li> <li>• Textile loops for tools.</li> <li>• Wide comfort padding.</li> </ul>	<p>Model: FA 10 402 00</p> <ul style="list-style-type: none"> <li>• 2 lateral 'D' rings for work positioning.</li> <li>• Fully adjustable.</li> <li>• Textile loops for tools.</li> <li>• Optimum width comfort padding.</li> </ul>
	
<b>Sit Work Positioning Belt</b>	<b>Suspension Trauma Relief Strap</b>
<p>Model: FA 10 403 00</p> <ul style="list-style-type: none"> <li>• 2 lateral 'D' rings for work positioning.</li> <li>• Waist level 'D' ring for rope access.</li> <li>• Fully adjustable.</li> <li>• Textile loops for tools.</li> <li>• Comfortable padding on waist belt and leg straps.</li> </ul>	<p>Model: FA 10 901 00</p> <ul style="list-style-type: none"> <li>• Extremely effective, specially designed to help relieve the negative effects of suspension trauma.</li> <li>• Compact and lightweight.</li> <li>• Does not hamper the activity of the worker while at work.</li> <li>• Allows the suspended worker to stand up in the harness to relieve pressure.</li> <li>• Easy to attach to the harness with the help of the textile loop and velcro provided.</li> <li>• Easy deployment, operation is foolproof.</li> </ul>
	
<b>Removal Dorsal Pad</b>	
<p>Model: FA 10 902 00</p> <ul style="list-style-type: none"> <li>• Foam with knitted mesh pad.</li> <li>• Designed to provide better comfort on harness.</li> <li>• Fits all kind of Kratos harness with 45mm webbing.</li> </ul>	
	
<b>Connectors</b>	
<b>Steel Screw-locking Karabiner</b>	<b>Steel Screw-locking Karabiner</b>
<p>Model: FA 50 101 17</p> <ul style="list-style-type: none"> <li>• Material : alloy steel.</li> <li>• Gate opening : 17mm.</li> <li>• Minimum breaking strength 23 kN.</li> </ul>	<p>Model: FA 50 102 17</p> <ul style="list-style-type: none"> <li>• Material : alloy steel.</li> <li>• Gate opening : 17mm.</li> <li>• Minimum breaking strength 23 kN.</li> <li>• With captive pin which ensures that the connector is not easily detached from the dorsal 'D' ring of the harness.</li> </ul>
	



<b>Aluminium Screw-locking Karabiner</b>	<b>Aluminium Screw-locking Snap Hook</b>
<p>Model: FA 50 103 22</p> <ul style="list-style-type: none"> <li>• Material : aluminium alloy.</li> <li>• Gate opening : 22.5mm.</li> <li>• Minimum breaking strength 20 kN.</li> </ul>	<p>Model: FA 50 104 24</p> <ul style="list-style-type: none"> <li>• Material : aluminium alloy.</li> <li>• Gate opening : 24mm.</li> <li>• Minimum breaking strength 20 kN.</li> </ul>
<b>Aluminium Quarter Turn-locking Karabiner</b>	<b>Steel Snap Hook</b>
<p>Model: FA 50 201 22</p> <ul style="list-style-type: none"> <li>• Material : aluminium alloy.</li> <li>• Gate opening : 22mm.</li> <li>• Minimum breaking strength 20 kN.</li> </ul>	<p>Model: FA 50 202 17</p> <ul style="list-style-type: none"> <li>• Material : alloy steel.</li> <li>• Gate opening : 17mm.</li> <li>• Minimum breaking strength 23 kN.</li> </ul>
<b>Steel Swivel Snap Hook with Load Indicator</b>	<b>Aluminium Quarter Turn-locking Snap Hook</b>
<p>Model: FA 50 203 11</p> <ul style="list-style-type: none"> <li>• Material : alloy steel.</li> <li>• Gate opening : 11.5mm.</li> <li>• Minimum breaking strength 23 kN.</li> <li>• In the event of a fall the indicator band will change from green to red serving as a warning signal before subsequent use.</li> </ul>	<p>Model: FA 50 206 22</p> <ul style="list-style-type: none"> <li>• Material : aluminium alloy.</li> <li>• Gate opening : 22.5mm.</li> <li>• Minimum breaking strength 20 kN.</li> </ul>
<b>Steel Scaffold Hook</b>	<b>Aluminium Rebar Hook</b>
<p>Model: FA 50 207 55</p> <ul style="list-style-type: none"> <li>• Material : forged alloy steel.</li> <li>• Gate opening : 55mm.</li> <li>• Minimum breaking strength 23 kN.</li> </ul>	<p>Model: FA 50 208 60</p> <ul style="list-style-type: none"> <li>• Material : aluminium alloy.</li> <li>• Gate opening : 60mm.</li> <li>• Minimum breaking strength 23 kN.</li> </ul>
<b>Anchorage Hook</b>	<b>Anchorage Hook</b>
<p>Model: FA 50 209 14</p> <ul style="list-style-type: none"> <li>• Material : stainless steel.</li> <li>• Gate opening : 140mm.</li> <li>• Minimum breaking strength 23 kN.</li> </ul>	<p>Model: FA 50 210 11</p> <ul style="list-style-type: none"> <li>• Material : stainless steel.</li> <li>• Gate opening : 110mm.</li> <li>• Minimum breaking strength 23 kN.</li> </ul>
<b>Anchorage Hook</b>	<b>Aluminium Snap Hook</b>
<p>Model: FA 50 211 75</p> <ul style="list-style-type: none"> <li>• Material : stainless steel.</li> <li>• Gate opening : 75mm.</li> <li>• Minimum breaking strength 23 kN.</li> </ul>	<p>Model: FA 50 212 21</p> <ul style="list-style-type: none"> <li>• Material : aluminium alloy.</li> <li>• Gate opening : 21mm.</li> <li>• Minimum breaking strength 23 kN.</li> </ul>
<b>Steel Tower Hook</b>	<b>Aluminium Rebar Hook</b>
<p>Model: FA 50 213 80</p> <ul style="list-style-type: none"> <li>• Material : alloy steel.</li> <li>• Gate opening : 80mm.</li> <li>• Minimum breaking strength 23 kN.</li> </ul>	<p>Model: FA 50 214 60</p> <ul style="list-style-type: none"> <li>• Material : aluminium alloy.</li> <li>• Gate opening : 60mm.</li> <li>• Minimum breaking strength 23 kN.</li> </ul>









<p><b>Steel Triple-locking Karabiner</b></p> <p>Model: FA 50 301 23</p> <ul style="list-style-type: none"> <li>• Material : alloy steel.</li> <li>• Minimum opening : 23mm.</li> <li>• Minimum breaking strength : 23 kN.</li> </ul> 	<p><b>Aluminium Triple action-locking Karabiner</b></p> <p>Model: FA 50 302 22</p> <ul style="list-style-type: none"> <li>• Material : aluminium alloy.</li> <li>• Gate opening : 22mm.</li> <li>• Minimum breaking strength 20 kN.</li> </ul> 
<p><b>Triple Action Locking Aluminium Snap Hook</b></p> <p>Model: FA 50 303 22</p> <ul style="list-style-type: none"> <li>• Material : aluminium alloy.</li> <li>• Gate opening : 22.5mm.</li> <li>• Minimum breaking strength 20 kN.</li> </ul> 	
<p><b>Anchorage</b></p>	
<p><b>7 ft Tripod</b></p>	<p><b>10 ft Tripod</b></p>
<p>Model: FA 60 001 00</p> <ul style="list-style-type: none"> <li>• Telescopic legs adjustable height from 1.15 mtrs to 2.15 mtrs.</li> <li>• Wheelbase: 1.5 mtrs.</li> <li>• Maximum load capacity: 200 kgs.</li> <li>• Also available in 10 ft (Model: FA 60 002 00).</li> </ul> 	<p>Model: FA 60 002 00</p> <ul style="list-style-type: none"> <li>• Telescopic legs adjustable height from 1.9 mtrs to 2.9 mtrs.</li> <li>• Wheelbase: 1.8 mtrs.</li> <li>• Maximum load capacity: 200 kgs.</li> <li>• Also available in 7 ft (Model: FA 60 001 00).</li> </ul> 
<p><b>Rescue and work winch</b></p> <p>Model: FA 60 003 00</p> <ul style="list-style-type: none"> <li>• 4.8mm dia x 20 mtr galvanised steel wire rope.</li> <li>• Load capacity 135 kgs.</li> </ul> 	<p><b>Anchorage Webbing Sling</b></p> <p>Model: FA 60 004 15</p> <ul style="list-style-type: none"> <li>• 44mm wide webbing with stainless steel 'D' ring at each end.</li> <li>• Minimum breaking strength 15 kN.</li> </ul> 
<p><b>Anchorage Webbing Sling</b></p>	<p><b>Anchorage Webbing Sling</b></p>
<p>Model: FA 60 005 06</p> <ul style="list-style-type: none"> <li>• 30mm wide polyester webbing.</li> <li>• Length 0.6 mtrs.</li> <li>• Minimum breaking strength 10 kN.</li> </ul> 	<p>Model: FA 60 005 10</p> <ul style="list-style-type: none"> <li>• 30mm wide polyester webbing.</li> <li>• Length 1.0 mtr.</li> <li>• Minimum breaking strength 10 kN.</li> </ul> 
<p><b>Anchorage Webbing Sling</b></p>	<p><b>Anchorage Steel Wire Rope Sling</b></p>
<p>Model: FA 60 005 15</p> <ul style="list-style-type: none"> <li>• 30mm wide polyester webbing.</li> <li>• Length 1.5 mtrs.</li> <li>• Minimum breaking strength 10 kN.</li> </ul> 	<p>Model: FA 60 006 10</p> <ul style="list-style-type: none"> <li>• Designed for structures with sharp edges.</li> <li>• 8mm PVC coated galvanised steel wire rope.</li> <li>• Steel thimble eyes at each end.</li> <li>• Minimum breaking strength 15 kN.</li> <li>• Length 1.0 mtr.</li> </ul> 



<b>Anchorage Steel Wire Rope Sling</b>	<b>Temporary lifeline</b>
<p>Model: FA 60 006 20</p>  <ul style="list-style-type: none"> <li>• Designed for structures with sharp edges.</li> <li>• 8mm PVC coated galvanised steel wire rope.</li> <li>• Steel thimble eyes at each end.</li> <li>• Minimum breaking strength 15 kN.</li> <li>• Length 2.0 mtrs.</li> </ul>	<p>Model: FA 60 007 00</p>  <ul style="list-style-type: none"> <li>• Secures an operator throughout travel.</li> <li>• Horizontal lifeline in 30mm webbing.</li> <li>• Forked ends in order to either anchor to a structure without the need to add anchorage sling or hang directly on adapted anchorage point.</li> <li>• Steel ratchet to put the system into tension after adjusting the required length.</li> <li>• Supplied with 2 steel snap hooks.</li> <li>• Adjustable length from 2 mtrs to 20 mtrs.</li> <li>• Minimum breaking strength 25 kN.</li> </ul>
<b>Beam Anchor</b>	<b>Anchorage Point</b>
<p>Model: FA 60 008 00</p>  <ul style="list-style-type: none"> <li>• Material : aluminium &amp; brass.</li> <li>• Minimum breaking strength 23 kN.</li> </ul>	<p>Model: FA 60 009 00</p>  <ul style="list-style-type: none"> <li>• Material : aluminium alloy.</li> <li>• Designed to be used according to the three axis.</li> <li>• Finish : powder coating.</li> <li>• Minimum breaking strength : 22.5 kN.</li> </ul>
<b>Rescue &amp; rope access</b>	
<b>Grip Descender</b>	<b>Ascender Handle (Left)</b>
<p>Model: FA 70 001 00</p>  <p>Made up of Aluminium alloy. Black anodized finish . Ideal for descent on a single rope. It is equipped with a unique Self Braking System which initiates the brake as soon as the handle is released, or clasped too tightly. Works on 10-11 mm diameter Kernmantle rope. Max speed : 2 m/s Weight : 345 gms</p>	<p>Model: FA 70 002 00</p>  <p>Made up of Aluminium alloy. Black anodized finish .</p>
<b>Ascender Handle (Right)</b>	<b>Figure of 8</b>
<p>Model: FA 70 003 00</p>  <p>Made up of Aluminium alloy. Green anodized finish . Designed for rope climbing, it locks with one hand for comfortable use. It works on kernmantle rope 9-11 mm. For use on single rope 9 to 11 mm. Weight : 196 gms</p>	<p>Model: FA 70 004 00</p>  <p>Made up of Aluminium alloy. Anodized finish. Manual descender for a self evacuation. It works on kernmantle rope 9-11 mm. Inner diam 52 mm and 26 mm. Height - 145 mm. Poids : 130 gms Breaking Load &gt; 50 KN.</p>

<p><b>Evacuation Triangle</b></p>	<p><b>Easy Seat</b></p>
<p>Model: FA 70 005 00</p> <p>To be used for rescue of injured personnel. Contains 3 metallic D-Rings at attachment elements. Size : Universal</p>	<p>Model: FA 70 006 00</p> <p>Is an accessory to harness having a Ventral D-Ring for easy attachment of Karabiner. Ergonomic ,Comfortable Working chair with Aluminium reinforcement inside Made up of 44 mm <b>Polyester Webbing</b> Breaking strength &gt; 23 kN Metal Components made up of high strength steel. Weight 1280gms</p>
<p><b>Pilot Chair</b></p>	<p><b>Spreader Bar</b></p>
<p>Model: FA 70 007 00</p> <p>Ergonomic and comfortable working chair. For vertical ascent and descent. Spreader Bar available as optional accessory.</p>	<p>Model: FA 70 007 01</p> <p>Is available as an optional accessory to the Pilot Chair.</p>
<p><b>Single Aluminium Pulley</b></p>	<p><b>Kernmantle rope Semi Static 9mm</b></p>
<p>Model: FA 70 008 00</p> <p>Made up of Aluminium alloy. Green anodized finish . For use on maximum 12 mm rope. Anodized finish. Poids : 90 gms Breaking load &gt; 20 kN.</p>	<p>Model: FA 70 009 99</p> <p>Made up of polyamide. Available in various length on request. Maximum Roll Size : 300mts</p>
<p><b>Kernmantle rope Semi Static ø10.5mm</b></p>	<p><b>Kernmantle rope Semi Static ø11mm</b></p>
<p>Model: FA 70 010 99</p> <p>Made up of polyamide. Available in various length on request. Maximum Roll Size : 300mts</p>	<p>Model: FA 70 011 99</p> <p>Made up of polyamide. Available in various length on request. Maximum Roll Size : 300mts</p>
<p><b>Kernmantle rope Semi Static ø12mm</b></p>	
<p>Model: FA 70 012 99</p> <p>Made up of polyamide. Available in various length on request. Maximum Roll Size : 300mts</p>	
<p><b>Kits</b></p>	
<p><b>Restraint kit at work</b></p>	<p><b>Scaffolder kit</b></p>
<p>Model: FA 80 001 00</p> <p>Minimalist, but complete this set must be used where there is no risk of a fall, in restrained work.</p>	<p>Model: FA 80 002 00</p> <p>This set is essential in our range and should be used when working at heights over 6 meters.</p>

<b>Roof, carpenter, waterproofer kit</b>	<b>Facades kit, bridge, rock face</b>
<p>Model: FA 80 003 00</p> <p>This set is essential in our range and should be used when working at heights over 6 meters.</p> 	<p>Model: FA 80 004 00</p> <p>Multi-use and very comfortable, this set allows large vertical movements.</p> 
<b>Steel construction kit, crane boom</b>	<b>Pylon, tower kit</b>
<p>Model: FA 80 005 00</p> <p>Indispensable when working with movements which require hooking/unhooking frequently.</p> 	<p>Model: FA 80 006 00</p> <p>Complete, comfortable and multipurpose this set also includes a work positioning function.</p> 
<b>Facade, roof, window cleaner kit</b>	<b>Facade, roof, window cleaner kit</b>
<p>Model: FA 80 007 10</p> <p>Essential when working on roofs thanks to the manual locked position.</p> 	<p>Model: FA 80 007 20</p> <p>Essential when working on roofs thanks to the manual locked position.</p> 
<b>Facade, roof, window cleaner kit</b>	<b>Basket, scaffold kit</b>
<p>Model: FA 80 007 30</p> <p>Essential when working on roofs thanks to the manual locked position.</p> 	<p>Model: FA 80 008 00</p> <p>A complete and economical solution for low-level interventions.</p> 
<b>Energy Absorbing Lanyards</b>	
<b>Energy Absorber</b>	<b>Energy Absorber</b>
<p>Model: FA 30 000 35</p> <ul style="list-style-type: none"> <li>• 35 mm wide webbing shrink wrapped.</li> <li>• Reduces the impact of fall to less than 6 kN.</li> <li>• To be used with a restraint lanyard (EN354).</li> </ul> 	<p>Model: FA 30 000 45</p> <ul style="list-style-type: none"> <li>• 44 mm wide webbing shrink wrapped.</li> <li>• Reduces the impact of fall to less than 6 kN.</li> <li>• To be used with a restraint lanyard (EN354).</li> </ul> 
<b>Energy Absorber</b>	<b>Forked Twisted Rope Lanyard</b>
<p>Model: FA 30 100 15</p> <ul style="list-style-type: none"> <li>• 12mm dia polyamide twisted rope lanyard.</li> <li>• 44 mm wide webbing energy absorber shrink wrapped.</li> <li>• Reduces the impact of fall to less than 6 kN.</li> <li>• Loops protected by an abrasion resistant thimble.</li> <li>• Spliced end protected with strong transparent covering sleeve.</li> </ul> 	<p>Model: FA 30 200 15</p> <ul style="list-style-type: none"> <li>• 12mm dia polyamide twisted rope lanyard.</li> <li>• 44mm wide webbing energy absorber shrink wrapped.</li> <li>• Reduces the impact of the fall to less than 6kN.</li> <li>• Spliced end protected with strong transparent covering sleeve.</li> </ul> 

<b>Webbing Lanyard 44mm</b>	<b>Webbing Lanyard 35mm</b>
<p>Model: FA 30 300 15</p> <p>-Energy absorber in 44 mm wide webbing which reduces the impact of the fall less than 6 kN -44 mm wide polyester webbing lanyard -Loops protected by an abrasion resistant tubular webbing.</p> 	<p>Model: FA 30 304 18</p> <p>-Energy absorber in 35 mm wide webbing which reduces the impact of the fall less than 6 kN -30 mm wide <b>polyester webbing</b> lanyard -Loops protected by an abrasion resistant tubular webbing.</p> 
<b>Forked Webbing Lanyard</b>	<b>Shock Absorbing Kernmantle Rope Lanyard 1.5 mtr</b>
<p>Model: FA 30 400 15</p> <p>- Energy absorber in 35 mm wide webbing which reduces the impact of the fall less than 6 kN - 30 mm wide polyester webbing lanyard - Loops protected by an abrasion resistant tubular webbing</p> 	<p>Model: FA 30 400 15</p> <p>- Energy absorber in 35 mm wide webbing which reduces the impact of the fall less than 6 kN - 30 mm wide polyester webbing lanyard - Loops protected by an abrasion resistant tubular webbing</p> 
<b>'Y' Forked Kernmantle Rope Shock Absorbing Lanyard 1.5 mtr</b>	<b>Expandable Lanyard</b>
<p>Model: FA 30 600 15</p> <ul style="list-style-type: none"> <li>• 12mm kernmantle rope with 44mm wide webbing shock absorber &amp; karabiner at one end and scaffold hooks at the other ends.</li> <li>• Loops protected by an abrasion resistant thimble.</li> <li>• Stitching protected with a strong transparent sleeve.</li> <li>• Reduces the impact of a fall to less than 6 kN.</li> </ul> 	<p>Model: FA 30 701 20</p> <ul style="list-style-type: none"> <li>• Energy absorber in 35 mm wide webbing which reduces the impact of the fall less than 6 kN.</li> <li>• 44 mm wide polyester expandable elasticated webbing lanyard.</li> <li>• Loops protected by an abrasion resistant tubular webbing. Expanded length : 2 m Relaxed length : 1,4 m</li> </ul> 
<b>Expandable Lanyard</b>	<b>Expandable Lanyard</b>
<p>Model: FA 30 702 20</p> <ul style="list-style-type: none"> <li>• Energy absorber in 35 mm wide webbing which reduces the impact of the fall less than 6 kN.</li> <li>• 44 mm wide polyester expandable elasticated webbing lanyard.</li> <li>• Loops protected by an abrasion resistant tubular webbing. Expanded length : 2 m Relaxed length : 1,4 m</li> </ul> 	<p>Model: FA 30 703 20</p> <ul style="list-style-type: none"> <li>• Energy absorber in 35 mm wide webbing which reduces the impact of the fall less than 6 kN.</li> <li>• 44 mm wide polyester expandable elasticated webbing lanyard.</li> <li>• Loops protected by an abrasion resistant tubular webbing. Expanded length : 2 m Relaxed length : 1,4 m</li> </ul> 
<b>Expandable Lanyard</b>	
<p>Model: FA 30 703 20</p> <ul style="list-style-type: none"> <li>• Energy absorber in 35 mm wide webbing which reduces the impact of the fall less than 6 kN.</li> <li>• 44 mm wide polyester expandable elasticated webbing lanyard.</li> <li>• Loops protected by an abrasion resistant tubular webbing. Expanded length : 2 m Relaxed length : 1,4 m</li> </ul> 